

compact

lightweight

powerful

versatile



Alpha System

M8 MID/HI

PRODUCT FEATURES

High power Mid/Hi module 143dB peak SPL @ 1m) using advanced co-axial waveguides with multipath phase devices.

Horn loaded 2 x 10" MF and 1 x 3" HF components on medium-Q waveguide provide 75° x 45° dispersion for medium throw applications, frequency response 190Hz-19kHz. User configurable, rotatable horn.

Active 2-way operation with NX241 Digital TDController ensures reliable, linear operation.

Baltic birch cabinet and high performance honeycomb composite construction.

Available in dark grey carpet covering or textured black paint.

Integrated flying system hardware for Crossbow flying system or standard aircraft fittings.

Ergonomically designed for flying or ground stacking, easy touring handling and truck packs.

ALPHA SYSTEM APPLICATIONS

Large scale touring or installed PA for stadiums, arenas, clubs, A/V, and theater.

Industry standard touring PA with global support network.

All Alpha products are 22.5° trapezoid shaped cabinets with the same width and depth; height is in multiples of 200 mm (7 7/8")



600mm
23.625"



Alpha System Components

B1 Bass

M3 Mid/Hi

▶ M8 Mid/Hi

S2 Subbass



NX241 Digital TDController

The Alpha M8 is an advanced high power, medium-Q Mid/Hi module that has the same form factor as the high-Q M3, allowing user selectable dispersion characteristics appropriate to the application. The M8 uses two exponential horn loaded 10" MF drivers and a constant directivity horn loaded 3" HF driver giving 75° x 45° dispersion, the horn may be rotated with the wider dispersion in the horizontal or vertical plane. Operated as a 2-way active system for ultimate performance and control, the Alpha M8 has a frequency response of 190Hz-19kHz. Stacked or flown in arrays together with an Alpha B1 Bass, the Alpha M8 delivers outstanding performance as part of a precision, compact, large scale system.

The Alpha System is a range of advanced technology modular, compact, high power loudspeaker modules tailored for a wide range of touring and installed sound reinforcement applications, from clubs and theaters to large scale live events. Like all Nexo products, Alpha System components are designed to work with advanced electronic processors, guaranteeing consistent performance and reliability of the highest standard.

NEXO

I N N O V A T E

compact

lightweight

powerful

versatile

Alpha System

M8 MID/HI

PRODUCT FEATURES

Components	MF: 2 x 10" (25 cm) 8 Ohm 3" voice coil driver + Dual Ring Phase Plug, Composite Horns HF: + Coaxial Mount Waveguide.
Height x Width x Depth	600 x 689 x 754mm (23 5/8"x 27 1/8"x 29 11/16")
Shape	22.5° trapezoid
Weight	Net: 57 kg (126 lbs) With wheelboard: 64 kg (141 lbs)
Connectors	2 x SPEAKON 8 pole (In & Loop Thru) Wiring: 1+ & 1- (VLF), 2+ & 2- (LF), 3+ & 3- (MF), 4+ & 4- (HF) 1 x SPEAKON 4 pole (to B1 & S2) Wiring: 1+ & 1- (VLF), 2+ & 2- (LF)
Construction	The self supporting MF/HF module is built from high performance honeycomb composites. Baltic Birch Ply finished with dark grey carpet. Textured, polyurethane black paint coating also available.
Fittings:	Handles Front finish Flying Points & Fixed Installation
	2 Metal Bar Handles Acoustic foam on perforated steel grille (77% transparent) Crossbow Flying System cabinet hardware; 4 Flying Tracks on front (7 positions in 2.5° steps), top to bottom steel back plate, 4 Flying Tracks on back (Hinge Fixing), Internal top to bottom & left to right steel links. Crossbow flying tracks can also receive standard aircraft fittings.

SYSTEM SPECIFICATIONS Alpha M8 with NX241 Digital TDController

Frequency Response [a]	190 Hz – 19 kHz \pm 3dB
Usable Range @-6dB [a]	150 Hz – 20 kHz
Sensitivity 1W @ 1m [b]	108 dB SPL Nominal
Nominal Peak SPL @ 1m [b]	143 dB Peak
Dispersion [c]	75° x 45° (Horn rotatable)
Directivity : Q & DI [c]	Q: 20 Nominal DI: 13 dB Nominal (f > 630 Hz)
Nominal Impedance	MF: 12 Ohms (15.5 min) HF: 12 Ohms (8.0 Ohms min)
Recommended Amplifiers	MF: 650 to 900 Watts into 12 Ohms HF 350 to 500 Watts into 12 Ohms

SYSTEM OPERATION

Electronic Controller	The Alpha M8 Mid/Hi must be used with a Nexo NX241 Digital TDController. Use without a properly connected Controller will result in poor sound quality and may damage the components.
Subbass	The Alpha M8 Mid/Hi and B1 Bass can be used with or without the optional S2 Subbass. Active four-way operation with the S2 is included in the NX241.

SHIPPING & ORDERING

Ordering	Alpha M8 carpet finished and ready to fly (without wheelboard) = Ref: AL.M8-CF. Other versions please refer to your Nexo agent.
Packaging	Alpha M8s are sold as single items and in multiples thereof.
Shipping Weight & Volume	Packaging will vary according to carpet or paint finish & quantity ordered. Please refer to your Nexo agent.
Accessories	Crossbow Flying System, refer to the Crossbow specs. Wheelboard = Ref: AL.WB1.


As part of a policy of continual improvement, NEXO reserves the right to change specifications without notice.

[a] Response curves & data : Anechoic Far Field above 200Hz. Half-Space Anechoic below 200Hz. Usable Range Data: Frequency response capability with TD crossover slopes removed.

[b] Sensitivity & Peak SPL data : will depend on spectral distribution. Measured with band limited Pink Noise. Refers to the specified \pm 3dB range. Data are for speaker + processor + recommended amplifier combinations.

[c] Directivity curves & data: 1/3 octave smoothed frequency response, normalised to On-Axis response. Data obtained by computer processing of off axis response curves.

approved product



LIMITED WARRANTY

Nexo loudspeakers and electronics are covered against defects in workmanship or materials for a period of two (2) years from the original date of purchase. At the option of Nexo, the defective item will be repaired/replaced with no charge for materials/labor. The item is to be adequately packaged and dispatched, pre-paid, to a Nexo authorized distributor/service center. Unauthorized repair shall void the warranty. This Nexo warranty does not cover cosmetics or finish and does not apply to any items which in Nexo's opinion have failed due to user abuse, accidents, modifications or any type of misuse.

www.nexo-sa.com

NEXO is one of the world's leading sound reinforcement loudspeaker manufacturers. Founded in 1979, the company is dedicated to crafting practical solutions with solid engineering. Each new design begins with a proprietary sophisticated computer simulation process that allows every parameter to be extensively modelled and simulated, leading to breakthrough cost and performance gains.

Nexo's comprehensive product line includes loudspeakers, analogue and digital control electronics and amplification; all designed to deliver consistent sound quality and long-term reliability for a broad range of applications. Continuing research drives all new product development to deliver on our promise; **Sonic Innovation That Works.**

NEXO S.A.
154 allée des Erables
ZAC de PARIS NORD II B.P. 50107
F-95950 Roissy CDG CEDEX
France

Tél: +33 1 48 63 19 14
Fax: +33 1 48 63 24 61
E-mail: info@nexo.fr

NEXO Limited
9 Lyon Road
Walton on Thames
Surrey
KT12 3PU
United Kingdom

Tel: +44 1932 886 007
Fax: +44 1932 886 008
E-mail: info@nexo-sa.com

Nexo USA, Inc.
2165 Francisco Blvd.
Suite E2
San Rafael, CA 94901

Phone: 1-415-482-6600
Fax: 1-415-482-6110
E-mail: info@nexo.cc

NEXO Far East Pte Ltd
101 Lorong, 23 Geylang
#06-04 Prosper House
Singapore 388399

Tel: +65 742 5660
Fax: +65 742 8050
E-mail: info@nexo-sg.com

I N N O V A T E